

Holland wear patch reduces hardfacing costs and keeps your equipment moving




MODERATE IMPACT RESISTANT WEAR PATCH

Applications: Dozer
Moldboards and Sidearm;
Loader Bucket Side Protection
and Bottom between Skids;
Impact Resistant Materials
including Chutes; Drag Lines;
Shovels; Excavators; Truck
Beds; Log Forks; and various
other applications that are
subject to impact.



MODERATE IMPACT 45 RESISTANT WEAR PATCH

Applications: Shovel Buckets; Drag Lines; Excavators; Dozers and many other high wear applications subject to impact.




HIGH ABRASION WEAR PATCH

Applications: Loader Bucket Side Protection; Elevating and Push-Pull Scrapers; Crusher Chutes (note: WP-340 will normally crush if worn out because of their hardness); Material Deflector Plates; Drag Lines; Excavators; Paving Machine Chain Covers; Return Guides; Conveyor Troughs; Baffels; Pugmills; Backhoe Buckets and many other applications.

* Also available in high impact 3/8" thickness.


HWP-812-38=3/8x8x12 - 10 lbs




HIGH ABRASION WEAR LIPS

Applications: Loader Buckets; Vertical Edges; Backhoe, Elevator and Excavator Buckets; Mixing Paddles and many other abrasive applications requiring special angles.

HIGH ABRASION WEAR PATCH Applications: Same as HWP340 Smaller width is better suited to fit contoured surfaces such as round troughs or flat surfaces where small area protection is required. WP-154 is ideal for Asphalt Paver Wear Slats.





> HWP259

HIGH ABRASION BEVEL WEAR LIPS
Abrasion Applications for Moldboard Adaptors
on Loaders, Drag Lines and Shovels. Also fits
on Skid Bevels for Mowers, Cultivator Skids
and many other applications. Also available
in 1/4" for heavy duty applications.

PART NUMBER	DESCRIPTION	THICKNESS	WIDTH	LENGTH	WEIGHT
WP-154	Flat Wear Patch	.1875"	1.50"	4.00°	.32 lbs.
WP-342	Flat Cone Wear Patch	.1875"	2.50-3.00*	4.00"	.58 lbs.
WP-340	Flat Wear Patch	.1875"	3.00"	4.00"	.64 lbs.
WP-450	Flat Wear Patch	.2500"	4.00"	5.00"	1.42 lbs.
WP-570	Flat Wear Patch	.2500*	5.00"	7,00"	2.48 lbs.
WP-340-38	Flat Wear Patch	.3750*	3.00"	4.00"	1.28 lbs.
WP-570-38	Flat Wear Patch	.3750"	5.00"	7:00"	3.72 lbs.
WP-254	30 deg. Bucket Lip	.1875"	2.50"	4.00"	.74 lbs.
WP-255	RH Corner Bucket Lip	.1875"	2.75"	5.25"	.86 lbs.
WP-256	LH Corner Bucket Lip	.1875"	2.75"	5.25"	.86 lbs.
WP-257	45 deg, Bucket Llp	.1875"	2.50"	4.00"	.80 lbs.
WP-258	90 deg. Bucket Lip	.1875"	2.50"	4.00"	.64 lbs.
WP-259	30 deg. Moldboard Lip	.1875"	2.50*	4.00"	.60 lbs.
WP-259-HD	Heavy Duty 30 deg. Mold.	.2500"	2.50"	4.00"	.80 lbs.

HOLLAND EQUIPMENT COMPANY 2870 WEST 2100 SOUTH SALT LAKE CITY, UTAH 84119 (801) 972-1601 WWW.HOLLANDEQ.COM